

Robotic Residual Stress Measuring System With 3D Scanner

Stress mapping on curved surface
Versatile Oscillation Options

APPLICATIONS

- Stress mapping
- Hardness mapping with FWHM
- Large grain samples
- Additive Manufacturing
- Heat effects analysis on welding

FEATURES

- Nondestructive stress measurement
- Automatic mapping with 3D scan
- Versatile oscillation



For more information,
visit <https://www.pulstec.net/>

PULSTEC

Robotic Residual Stress Measuring System With 3D Scanner

FEATURES & BENEFITS

Comprehensive Mapping:
Versatile Oscillation Options:
Automatic mapping saves your time:
Intuitive Design:
Advanced High-Sensitivity 3D Detection:
No Antihalation Spray Required:
High Accuracy & Stability:
Precision in Details:

SPECIFICATIONS

XRD stress analyzer:

μ -X360s

Cos-Alpha method for stress calculation

Cr, V, Mn, Co, Cu tube replaceable

Collimator replaceable

3D scanner:

TDS-320L

Laser 3D scanner with triangulation method

Robot:

MOTOMAN-GP8

Shielding Box/Robot Enclosure:

W=1,500, H=1,800, D=1,500mm

Maximum sample size: 400 x 400 x 400mm

Maximum sample weight: Approx. 30 kg


Optional Motorized Rotation Stage

No radiation leaks

Power supply:

Single phase AC 200/230V (-15% to +10%)

100 to 240V AC (-10% to +6%)



Pulstec USA, Inc.

28175 Haggerty Road, Suite140

Novi, MI 48377 USA

Tel: +1-310-316-8185, Fax: +1-310-316-9055

Contact: Toshi Suzuki

toshi@pulstec.net

Pulstec Industrial Co., Ltd.

7000-35, Nakagawa, Hosoe-cho, Hamana-ku,

Hamamatsu-City, Shizuoka Pref. 431-1304, Japan

Tel: +81-53-522-3611, Fax: +81-53-522-3666

<https://www.pulstec.co.jp/en/>